

## Dulux Spraypak Dazzle

NZDD1562

<b>Part A</b>	898-LINE
---------------	----------


<b>Description</b>
DULUX Spraypak™ Dazzle is an ultra bright interior / exterior fluorescent paint for marking, safety, or decorative purposes. Out of direct sunlight DULUX Dazzle will last for years.

<b>Features</b>
<ul style="list-style-type: none"> <li>• Quick Dry</li> <li>• Bright Fluorescent colour range</li> <li>• Versatile application</li> <li>• Low Aromatic</li> </ul>

<b>Benefits</b>
<ul style="list-style-type: none"> <li>• Touch Dry in 5 minutes</li> <li>• One product paints most common surfaces (except some plastics)</li> <li>• Can be handled in 10 minutes.</li> </ul>

<b>Uses</b>
DULUX Spraypak™ Dazzle can be used on most common surfaces. To ensure surface compatibility, spot test on an inconspicuous area before application.

<b>Performance Guide</b>			
<b>Weather</b>	Interior or exterior use.	<b>Heat Resistance</b>	Up to 120C. Premature yellowing and embrittlement occurs if heated to 120C continuously.
<b>Solvent</b>	Resists alcohols and aliphatic hydrocarbons. Film liable to attack from other strong solvents.		

<b>Typical Properties</b>			
<b>Gloss Level</b>	Flat	<b>Thinner</b>	Not Applicable
<b>Colour</b>	Range of colours (blue, green, orange, pink, red, scarlet, & yellow)	<b>Components</b>	1
<b>Number Of Coats</b>	1 or 2	<b>Toxicity</b>	Lead free. Dry film is non-toxic.
<b>Touch Dry</b>	5 Mins		
<b>Clean Up</b>	 Thinner		
<b>Application Method</b>	<b>Other:</b> Aerosol Spraypak		
<b>Application Conditions</b>	<b>Solids By Volume</b> 14  <b>Wet Film Per Coat (microns)</b> <b>Dry Film Per Coat (microns)</b> <b>Recoat Time (min)</b> 5 - 10 mins <b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>	<b>Min</b>     <b>Max</b>     <b>Recommended</b>	

Application Guide	
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, oil, wax, mould, loose or flaking paint. All rust, millscale should be removed by scraper or wire brush back to bare metal, dusted down and coated without delay as any rusting will detract from adhesion. Previously painted surfaces should be sanded lightly and wiped clean with a damp cloth. Ensure surface is dry before application. Protect adjoining surfaces from overspray.</li> </ul> <p>To achieve maximum brightness apply over a flat white background such as DULUX Spraypak™ Quick Dry Undercoat</p> <p>If applying to bare metal prime with DULUX Spraypak Precoat Grey Sanding Primer (not suitable for zinc and galvanised metal) or DULUX Spraypak Precoat Anti Corrosive Primer before undercoating.</p> <p>All strong solvent based paint systems, are prone to 'frying' previously painted surfaces and some plastics. To ensure surface compatibility test spray on an inconspicuous area first.</p>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>Before Spraying: Shake can well for at least 1 minute after the ball starts rattling and regularly during use. Temperature should be above 15C. Lower temperatures and high humidity will slow drying and affect the gloss.</li> </ul> <p>Applying: Hold can upright 25 to 30cm from the surface. To ensure surface compatibility test spray on an inconspicuous area first. Spray with smooth even strokes, parallel to the surface. Start away from and finish off the surface. Apply several light mist coats rather than one heavy coat, which can cause runs and sags. Each can will cover approximately 2 sq. metres depending on the surface porosity.</p> <p>Recoating: Where a second coat is required, recoat within 5 - 10 minutes.</p> <p>After Spraying: Prevent nozzle blocking by turning the can upside down and spraying until clear gas emerges. Also wipe the front of nozzle clean. Clean up any overspray while it is still wet using mineral turpentine.</p>

Health And Safety			
<b>MSDS Number</b>	22277	<b>Using Safety Precautions</b>	For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux Customer Service. Harmful by inhalation, in contact with skin and if swallowed. Intentional misuse by deliberately concentrating or inhaling contents can be harmful or fatal.
<b>MSDS Link</b>	<a href="http://msds.duluxgroup.com/pdf/shess-en-cds-020-000000022277.pdf">http://msds.duluxgroup.com/pdf/shess-en-cds-020-000000022277.pdf</a>		
<b>Flammability</b>	This product is flammable.	<b>Protective Equipment</b>	Wear eye protection, protective clothing, gloves and a suitable mask..
<b>Storage</b>	Keep out of reach of children. Store and use away from sources of heat and ignition.	<b>Disposal</b>	Do not incinerate or puncture can even when empty. Dispose of empty container in accordance with local authority regulations.
<b>Handling</b>	Avoid contact with skin and eyes and avoid breathing the vapour. Provide adequate ventilation. If using indoors keep windows open during use. Can may burst if exposed to sources of heat. Do not spray near naked flame.		
<b>In the case of emergency, please call 0800 734 607</b>			

Precautions And Limitations
<p>All preparation and painting must conform to AS2311: The Painting of Buildings.</p> <p>Do not apply at temperatures below 10C or when the temperature may fall below 10C during the drying period. Lower temperatures and high humidity will slow drying and affect the gloss.</p>

Transport And Storage			
<b>Pack A</b>	898-LINE	<b>Shipment Name</b>	Aerosols
<b>Size</b>	200 g	<b>Weight</b>	0.5 Kg
<b>UN Number</b>	1950	<b>Dangerous Goods Class</b>	2.1
<b>Package Group</b>	NA		

**Disclaimer**

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118